


Ziligen© Data Sheet

Name	Z 10/Z F/V1-20 ANT SE GREEN		
Stock Number		Update Date	Aug 18, 2021, 9:03:29 AM

Material Structure			
Total Thickness	2.00	+/- 0.10	
Number of Plies	2		
Tension Member Material	Low Noise PES		
Tension Member Structure	Rigid/Silent		
Weight	2.20		
Working Temperature	-10 °C	70 °C	

Top Cover	
Material	Pvc
Color	Green
Thickness	0.50 mm
Pattern	GL
Hardness	74 sHa
Electrostatic Properties	Nonantistatic
Internal Cover	
Material	Pvc
Bottom Cover	
Material	Low Noise Pes
Color	Natural
Thickness	0.00 mm
Pattern	-
Hardness	0 sHa
Electrostatic Properties	Antistatic

Profiles Application	
Top Cover	Yes
Bottom Cover	Yes
Sidewalls	No
Special Characteristic	
FDA Food	No
EU Food Regulation	No
Animal Oil Resistance	No
Vegetal Oil Resistance	No
Minerals Oil Resistance	No
Limited Resistance to Animal Oil and Greases	No
Excellent Abrasion Resistance	No
Cut Resistant	No
Low Friction	No
Silent Fabric	Yes
ATEX	No

Tension Member	
Breaking Load	120 N/mm
Working Load %1 Elongation	10 N/mm
Drum Diameter	
	40 mm
Splicing	
Overlap Splice	Yes
Z Splice	Yes
Mechanical Fasteners	A-36
Longitudinal Splice	
	Yes
Food App(TS-EN1186-1/15)	
	No

Support Surface	
Slider Bed	Yes
Rollers	No
Troughed Application	No
Friction Coeff. Bottom Cover	
On Steel	0.00 / 0.00
On Wood	0.00 / 0.00
On Plastic	0.00 / 0.00
Maximum Production Width	
	3000 mm
Flame Reterdant	
	No

Z-Splice Press Setup	
Upper Plate Temperature	155 °C
Lower Plate Temperature	155 °C
Stand By Time in Press	0 min
Press Pressure	3 bar
Glue	Pvc Foil

Overlap Splice Press Setup	
Upper Plate Temperature	155 °C
Lower Plate Temperature	155 °C
Stand By Time in Press	0 min
Press Pressure	3 bar
Glue	Pu + Hu

General Information	
Product Group	Pvc Conveyor Belt
Market Segment	

Create Date: Oct 29, 2021, 10:52:43 AM GMT

Create PDF